



























〈ダイヘン・パナソニック〉

# プラズマ切断機部品一覧

■ ダイヘン切断トーチ消耗部品一覧表

名称		CTL-0151 アングル形	CT-0351 アングル形	CT-0552 アングル形	CT-0701 アングル形	CTZW-0801 ロングハンドル形	CTZW-1201 ロングハンドル形
冷却方式		空冷	空冷	空冷	空冷	水冷	水冷
定格電流	A	15	35	55	70	80	120
定格使用時	%	50	60	60	60	100	100
ケーブル長	m	10	10	10	10	10	10
スタイル							
チップ							
		H1002F01	H705F04	H669G06	H669G05	H767F01	H839G03 H839K06
電極							
		H705F05		H669G11	H777G00	H839M00	H839P00
カップ							
		H705F03		H669G04	H767J00	H839G02	

■ パナソニック 3 型切断トーチ (空冷タイプ) 消耗品一覧表

品番		YT-03PD3	YT-03PE3	YT-06PD3	YT-06PE3	YT-08PD3	YT-08PE3	YT-08PDA3
形状	—	カーブド形	ペンシル形	カーブド形	ペンシル形	カーブド形	ペンシル形	カーブド形 (ロング)
冷却方式	—	空冷		空冷		空冷		
定格電流	A	35		60		80		
定格使用時	%	60		100		100		
ケーブル長	m	10		10		10		10
スタイル								
		カーブド形	ペンシル形	カーブド形	ペンシル形	カーブド形 (ロング)		
ショート用	チップ						電流値刻印付 TET-01110 (40A 用)	
		TET-00005 (35A 用)					線が1本(電流値刻印付) TET-01310 (60A 用)	
							線が2本(電流値刻印付) TET-01512 (80A 用)	
	電極						TET-02033 (40 ~ 80A 共用)	
ロング用	チップ						電流値刻印付 TET-01112 (40A 用)	
		TET-00003 (35A 用)					線が1本(電流値刻印付) TET-01311 (60A 用)	
							線が2本(電流値刻印付) TET-01513 (80A 用)	
	電極						TET-02040 (40 ~ 80A 共用)	
		TET-00004 (35A 用)						